



COMPONENT LIST			
L" DIM.	ITEM	MAKE FROM	DESCRIPTION
		P/N FT XX 6X48	CO WIRE .196 DIA.
2"		2X6X48	
4"		4X6X48	
6"		6X6X48	

GENERAL NOTES:

- A) MATERIAL TO BE DIPPED, PRE-GALVANIZED STEEL, TO AVOID THE FORMATION OF ZINC WISKERS.
- B) FINISH (CARBON STEEL WIRE ONLY).
 - 1) POLYESTER POWDER COATING 1.2 - 3.0 MILS THICK.
- C) DIMENSIONAL TOLERANCES
 - 1) GENERAL DIMENSIONS +/- 1/8" U.N.D.
 - 2) LENGTH +/- 1/4"
 - 3) WIDTH +/- 1/8"
 - 4) DEPTH +/- 1/8"
 - 5) ANGULAR FORMATION +/- 3 DEG.
 - 6) CAMBER SHALL NOT EXCEED 1/2" ON STANDARD 10' LENGTH.
 - 7) TWIST SHALL NOT EXCEED 1/2" ON STANDARD 10' LENGTH
- D) RIB VICE DIAMETER
 - 1) .197 (5MM) DIAMETER.
- E) LONGITUDINAL WIRE DIAMETER.
 - 1) .197 (5MM) DIAMETER
- F) CROSS SECTION AREA
 - AREA = (20 WIRES X .0438 IN²)= .876 IN²
 - UL MARKING = .8 IN²

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES.					DEBUR AND BREAK SHARP EDGES	
REVISION	NAME	CHANGE	DATE			
A	AF		5-12-10			
					MATERIAL:	
					WEIGHT:	

act
Access Cable Trays Inc.

TITLE:		FLOORFLEX-TRAY
DWG NO.		FT XX 6 X 48
		SHEET 1 OF 1