

FMSBC1 BORGMAN CLIP FIXTURE STABLIZING CLIPS PATENT PENDING





- WARNING:
 1. ERICO products shall be installed and used only as indicated in ERICO product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative.
 2. ERICO products must never be used for a purpose other than the purpose for which they were designed or in a manner that exceeds specified load ratings.
 3. All instructions must be completely followed to ensure proper and safe installation and performance.
 4. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.
 5. Products that are manufactured using spring steel components shall be used only in a non-corrosive indoor environment.
 6. All pipe supports, hangers, intermediate components and structural attachments must ONLY be used as described herein and are NEVER to be used for any other purpose.

NOTE: All load ratings are for static conditions and do not account for dynamic loading such as wind, water or seismic loads, unless otherwise noted.

The customer is responsible for:


a. Conformance to all governing codes.
b. The integrity of structures to which the products are attached, including their capability of safely accepting the loads imposed, as evaluated by a qualified engineer.
c. Using appropriate industry standard hardware as noted above.

All governing codes and regulations and those required by the job site must be observed.


Always use appropriate safety equipment such as eye protection, hard hat, and gloves as appropriate to the application.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.









- 1) FIXTURE STABILIZING CLIPS ACT AS OUT RIGGER TO STABILIZE LIGHT FIXTURES AND OTHER DEVICES.
- 2)THE CLIPS ALSO PREVENT CEILING TILES FROM LIFTING WHEN TRIM RINGS ARE INSTALLED.
- 3)TWO TO FOUR CLIPS PER INSTALLATION AS DETERMINED BY THE INSTALLER.
- 4)CLIPS CAN BE ADJUSTED BY BENDING TO INCREASE OR DECREASE PRESSURE ON TILE.



