```
TRADE NAME:
 MW HEAT SHRINK TUBING - COLORS
ID NUMBER/U.P.C.:
 80-6108-5593-6 00-51135-37693-5
ISSUED: February 02, 2001
SUPERSEDES: December 03, 1997
DOCUMENT: 07-1308-1
______
 1. INGREDIENT
                        C.A.S. NO.
                                   PERCENT
______
ADHESIVE LINED POLYOLEFIN TUBING...... Unknown
                                      100
._____
 2. PHYSICAL DATA
_____
BOILING POINT:.....N/A
VAPOR PRESSURE:..... N/A
VAPOR DENSITY:.....N/A
EVAPORATION RATE:.....N/A
SOLUBILITY IN WATER:..... N/A
SPECIFIC GRAVITY:..... ca. 1.0 Water=1
VISCOSITY:.....N/A
MELTING POINT:.....N/D
APPEARANCE AND ODOR:
 Tubing, various sizes, colors
 3. FIRE AND EXPLOSION HAZARD DATA
______
FLASH POINT:.....N/A
FLAMMABLE LIMITS - LEL:..... N/A
FLAMMABLE LIMITS - UEL:..... N/A
AUTOIGNITION TEMPERATURE:..... N/D
```

DIVISION: ELECTRICAL PRODUCTS DIVISION

MSDS: MW HEAT SHRINK TUBING - COLORS

February 02, 2001 PAGE 2

3. FIRE AND EXPLOSION HAZARD DATA (continued)

EXTINGUISHING MEDIA:

Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None known.

NFPA HAZARD CODES: HEALTH: 0 FIRE: 0 REACTIVITY: 0

UNUSUAL REACTION HAZARD: none

OSHA FIRE HAZARD CLASS: Not applicable

4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

None known.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Oxides of Sulfur, Aldehydes, Toxic Vapors, Gases or Particulates

Heating product beyond temperature recommended by instruction sheet may cause release of the following compounds: Benzene, Toluene, Formaldehyde, Acetaldehyde, Acetic Acid, and Vinyl Acetate.

5. ENVIRONMENTAL INFORMATION

SPILL RESPONSE:

Not applicable.

RECOMMENDED DISPOSAL:

Dispose of waste product in a sanitary landfill.

ENVIRONMENTAL DATA:

No data available.

February 02, 2001 PAGE 3

5. ENVIRONMENTAL INFORMATION (continued)

REGULATORY INFORMATION:

Volatile Organic Compounds: N/A. VOC Less H2O & Exempt Solvents: N/A.

Since regulations vary, consult applicable regulations or authorities before disposal.

EPCRA HAZARD CLASS:

FIRE HAZARD: NO PRESSURE: NO REACTIVITY: NO ACUTE: NO CHRONIC: NO

6. SUGGESTED FIRST AID

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

If skin contact with hot material occurs: DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Immediately flush affected area with plenty of cold water and cover with a clean dressing. Have burn treated by a physician.

INHALATION:

If signs/symptoms occur, remove person to fresh air. If signs/symptoms continue, call a physician.

IF SWALLOWED:

Drink two glasses of water. Call a physician.

7. PRECAUTIONARY INFORMATION

EYE PROTECTION:

AVOID EYE CONTACT WITH VAPORS OR SMOKE RESULTING FROM OVERHEATING OR WHEN USED IN CONFINED AREAS.

SKIN PROTECTION:

Avoid skin contact with hot material. Wear appropriate gloves, such as Nomex, when handling this material to prevent thermal burns.

RECOMMENDED VENTILATION:

Local exhaust is required for operations using large amounts of material. Conduct air monitoring to determine adequacy of ventilation. Use in a well-ventilated area. Provide sufficient ventilation to maintain emissions below recommended exposure limits. If exhaust ventilation is not adequate, use appropriate respiratory protection.

MSDS:	MW	HEAT	SHRINK	TUBING	-	COLORS
February		02,	2001			

February 02, 2001 PAGE 4

7. PRECAUTIONARY INFORMATION (continued)

WHEN USING THIS PRODUCT IN A CONFINED SPACE OR WHERE VENTILATION MAY BE INADEQUATE THEN RESPIRATORY PROTECTION MAY BE WORN. INADEQUATE VENTILATION OR CONFINED SPACES WOULD CAUSE VAPORS FROM HEATING OF THIS PRODUCT TO BE PRESENT IN THE USER'S BREATHING ZONE AND MAY CAUSE RESPIRATORY IRRITATION. EXCESSIVE HEATING OF THIS PRODUCT BEYOND THE RECOMMENDED APPLICATION TEMPERATURE OF 275 DEGREES FAHRENHEIT IS NOT RECOMMENDED AND MAY RESULT IN THERMAL DEGRADATION AND DECOMPOSITION PRODUCTS WHICH MAY RESULT IN ADVERSE HEALTH EFFECTS.

RESPIRATORY PROTECTION:

Avoid breathing of fumes. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half-mask organic vapor respirator with dust/mist prefilter.

PREVENTION OF ACCIDENTAL INGESTION:

Wash hands after handling and before eating.

RECOMMENDED STORAGE:

Store at room temperature. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Not applicable.

EXPOSURE LIMITS

INGREDIENT				VALUE	UNIT	TYPE	AUTH	SKIN*
ADHESIVE	LINED	POLYOLEFIN	TUBING	NONE	NONE	NONE	NONE	

* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

Vapors from heated material may cause eye irritation.

8. HEALTH HAZARD DATA (continued)

SKIN CONTACT:

Skin Burns (thermal, from contact with hot material): signs/symptoms can include burning pain, red and swollen skin, and blisters.

INHALATION:

Vapors of heated material may cause respiratory system irritation.

RESPIRATORY TRRITATION WOLLD NOT BE EXPECTED IN APPLICATIONS WHERE ADEOUATE VENTILATION AND PROPER APPLICATION (AT DESIGNATED TEMPERATURES) IS UTILIZED. EXCESSIVE HEATING AND INADEOUATE VENTILATION MAY RESULT IN EXPOSURE TO THERMAL DEGRADATION AND DECOMPOSITION PRODUCTS AS INDICATED IN SECTION 4 OF THIS MSDS UNDER "REACTIVITY DATA-HAZARDOUS DECOMPOSITION PRODUCTS".

IF SWALLOWED:

Ingestion is not a likely route of exposure to this product.

SECTION CHANGE DATES

PHYSICAL DATA SECTION CHANGED SINCE December 03, 1997 ISSUE