

YDPU2.E64007 Tubing, Extruded Insulating - Component

Page Bottom

Tubing, Extruded Insulating - Component

See General Information for Tubing, Extruded Insulating - Component

ZEUS INDUSTRIAL PRODUCTS INC

E64007

48 ORLANDO DR PO BOX 298

RARITAN, NJ 08869 USA

Cat. No.		Max V	Max Temp C R		Col ecognized		Max Temp Rated Oil Resistance *,°C	VW-1 Rated #
Polytetrafluoroethylene (PTFE).								
TFE-LW-150		150	200	Any	Any			Yes
TFE-TW-300		300	200 Any		_			Yes
TFE-SW-600		600	200	Any	Any —			Yes
TFE-HW-600		600	200	Any	Any –			Yes
Fluorinated ethylene propylene (FEP).								
FEP-TW-300		300	300 200		Апу			Yes
FEP-SW-600		600	500 200		Any			Yes
Cat. No.	Max V	Max Oper Temp			Col Recognized		Max Temp Rated Oil Resistance * °C	VW-1 Rated #
Heat shrinkal	ole polyt	etrafluoro	ethylene (PTFE).				
4:1	300	200	I	I				Yes
%2:1	300	200	п	п				Yes
Heat shrinkable fluorinated ethylene propylene (FEP).								
1.3:1	150	200	п		Any		-	_

^{*}Tubing is considered to comply with the optional oil resistant requirements only if it is so marked.

#Tubing is considered to comply with the optional VW-1 flammability requirements only if it is so marked.

Marking: Company name, the catalog number or equivalent, and temperature rating in degrees C appear on tags attached to both ends of the tubing or on the shipping spool label or smallest unit container.

<u>Last Updated</u> on 2002-06-28

Questions?

Notice of Disclaimer

Page Top

Copyright © 2008 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up

[%]Complies with UL224, 5th edition requirements.

Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2008 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

