

MATERIAL SAFETY DATA SHEET

GENERAL INFORMATION

PRODUCT NAME OR NUMBER (as it appears on label) Aqua-Gel® IIP Pourable Wire Pulling Lubricant		CATALOG NUMBER All "31" Series
MANUFACTURER'S NAME IDEAL INDUSTRIES, INC.		EMERGENCY TELEPHONE NO. (815) 895-5181
ADDRESS (Number, Street, City, State, Zip Code) Becker Place, Sycamore, IL 60178		
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD CLASS, HAZARD ID NO. (49 CFR 172.101) None		
CHEMICAL DESCRIPTION Polymer-based Mixture	FORMULA Proprietary	

SECTION I - INGREDIENTS

CAS REGISTRY NO.	%W	CHEMICAL NAME(S)*	Listed as a carcinogen in NTP, IARC or OSHA 1910(z) (specify)
7732-18-5	<95	Water	No
10043-35-3, 102-71-6, 141-43-5, 165445-22-7, 693-23-2	<1	Proprietary Mixture of Boric Acid, TEA, MEA, Succinic Acid Salt Ester, Dodecanedioic Acid	No
52-51-7	<0.1	2-Bromo-2-Nitropropane 1,3 Diol	No
9038-95-3	<10	Oxirane, Methyl-, Polymer With Oxirane, Monobutyl Ether	No
9003-11-6	<5	Poly(oxy-1,2-ethanediyl), a-(1-oxo-9-octadecenyl)-w-(1-oxooctadecyl)oxy-	No
3844-45-9 7757-82-6 7647-14-5	<0.01	Blue Pigment	No
1310-58-3	<2	20% Potassium Hydroxide	No

SECTION II - PHYSICAL DATA

BOILING POINT 212 °F 100 °C	SPECIFIC GRAVITY (H ₂ O=1) 0.98	PERCENT VOLATILE BY VOLUME (%) ~90
SOLUBILITY IN WATER Infinite	pH = 7.0 - 8.0	PERCENT SOLID BY WEIGHT (%) ~10
APPEARANCE AND ODOR Aqua pourable gel, mild color	IS MATERIAL: <input checked="" type="radio"/> LIQUID <input type="radio"/> GAS <input type="radio"/> SOLID <input type="radio"/> GEL <input type="radio"/> PASTE	

SECTION III - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT None	method used C.O.C	FLAMMABLE LIMITS	LEL None	UEL None
EXTINGUISHING MEDIA Use extinguishing media for surrounding materials.				
SPECIAL FIRE FIGHTING PROCEDURES None				
UNUSUAL FIRE AND EXPLOSION HAZARDS None				

* None of the chemical raw materials contained in this formulation are considered hazardous under the Federal Hazards Communication Standard 29 C. F. R 1910.1200

SECTION IV - HEALTH HAZARD INFORMATION

EFFECTS OF OVEREXPOSURE - Conditions to Avoid	None normally expected. Upon prolonged contact, may cause temporary eye discomfort.
THRESHOLD LIMIT VALUE	N.E.
PRIMARY ROUTES OF ENTRY Inhalation <input type="checkbox"/> Skin Contact <input checked="" type="checkbox"/> Other (specify)	
EMERGENCY FIRST AID PROCEDURES	
SKIN CONTACT:	Wash with soap and water.
EYE CONTACT:	Flush with water
INGESTION:	Do not induce vomiting. Consult physician or local poison control center.

SECTION V - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	Avoid prolonged storage at temperatures exceeding 190 F.
INCOMPATIBILITY (materials to avoid)			
Avoid strong oxidizers and nitrites.			
HAZARDOUS DECOMPOSITION PRODUCTS:			
In the unlikely event of combustion or dried residue, oxides of carbon and nitrogen may be released.			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	None

SECTION VI - SPILL AND LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED	Wipe up, shovel or vacuum spilled material. Clean up spills immediately as they can be dangerously slippery.
WASTE DISPOSAL METHOD	Comply with Federal, state and local regulations for solid landfill.
CERCLA (Superfund) REPORTABLE QUANTITY (in lbs)	N/A
RCRA HAZARDOUS WASTE NO. (40CFR 261.33)	N/A
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water)	1.2 gms / ltr
³ Theoretical _____ lb/gal	N/A
³ Analytical _____ lb/gal	N/A

SECTION VII - PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (specify type)	None normally required.	
VENTILATION	LOCAL EXHAUST (Specify Rate) None	SPECIAL None
	MECHANICAL (General) (Specify Rate) Recommended in closed areas.	OTHER None
PROTECTIVE GLOVES (specify type)	None normally needed -Neoprene if necessary	EYE PROTECTION (specify type)
OTHER PROTECTIVE EQUIPMENT	Eye fountain in work area is recommended but not necessary.	None normally required. Safely glasses or splash goggles recommended.

SECTION VIII - SPECIAL PRECAUTIONS


PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Store at temperatures between 40 -180 F. Avoid freezing.
OTHER PRECAUTIONS	Keep away from children, infants and pets.

SECTION IX - ADDITIONAL INFORMATION

Extreme temperatures of combustion or burning and contact with nitrites could result in the formation of nitrosamines which are potential carcinogens. This condition is unlikely to occur.

N/A = Not Applicable, N.E. = None Established

THIS MATERIAL SAFETY DATA SHEET PREPARED BY:

NAME	James R. MacMurdo	SIGNATURE 
TITLE	Mgr., Construction Market Development	
DATE	9/21/2010	