



# Structured Cable Products

DATE: 07/17/07

---

## SPECIFICATION SHEET

---

CONSTRUCTION : 14AWG SOLID BARE COPPER  
4 CONDUCTORS. OVERALL FOIL.

COLOR CODE : CC#17: BLACK, RED, WHITE, GREEN

INSULATION : 0.012 Inch, Low Smoke PVC

SHIELD/DRAIN : ALUM/POLY FOIL 100% COV. 24AWG 7/32 TC. DW.

CAPACITANCE : 54.4 pF/ft Nom.

VEL OF PROP : 55%

IMPEDANCE : 34 OHMS

RESISTANCE : 2.525 OHMS D.C. PER 1000 FT @ 68 DEG. F

TEMP/VOLTAGE : N/A

JACKET : RED, 0.014 Inch, LOW SMOKE PVC -- 0.241 Nom OD

CABLE WT : 66.92 Lb/1000Ft Approx (EXCLUDING REEL OR BOX)

PRINT LEGEND : E75610 FPLP/CL3P 14AWG (UL) MADE IN USA

UL : FPLP/CL3P

MISC : MADE IN USA

\* +/- 10% Manufacturing tolerance

\* On non-standard product, customer agrees to accept all lengths manufactured

---

APPROVED BY