

# Structured Cable Products

DATE: 07/17/07

---

## SPECIFICATION SHEET

---

CONSTRUCTION : 16AWG SOLID BARE COPPER  
4 CONDUCTORS. OVERALL FOIL.

COLOR CODE : CC#17: BLACK, RED, WHITE, GREEN

INSULATION : 0.010 Inch, 75 SR-PVC

SHIELD/DRAIN : ALUM/POLY FOIL 100% COV. 24AWG 7/32 TC. DW.

CAPACITANCE : 52.9 pF/ft Nom.

VEL OF PROP : 55%

IMPEDANCE : 35 OHMS

RESISTANCE : 4.016 OHMS D.C. PER 1000 FT @ 68 DEG. F

TEMP/VOLTAGE : N/A

JACKET : RED, 0.020 Inch, PVC -- 0.211 Nom OD

CABLE WT : 45.19 Lb/1000Ft Approx (EXCLUDING REEL OR BOX)

PRINT LEGEND : E75610 FPLR/CMR/CL3R 16AWG (UL) C(UL) CMG MADE IN USA

UL : FPLR/CMR

MISC : MADE IN USA

\* +/- 10% Manufacturing tolerance

\* On non-standard product, customer agrees to accept all lengths manufactured

---

APPROVED BY